

## WIRESLINE UNIT

### A1050561 – SlimSplit (Cabin / Winch Unit, Short Cab, Ex Zone 2, aluminum)

This design is a single piece wire line winch unit comprised of an enclosed short length operator cabin and single drum winch section. Unit can be transported as a single lift and is suitable for onshore operations in Zone 2 hazardous areas. The basic unit consist of an aluminum frame complete with composite panelling, integrated lifting pad eyes and forklift pockets (H x W = 90 x 280 mm). the aluminum frame is standard not painted. Only the steel part will be protected against corrosion with a high quality ASEP / Hempel developed single colour 3 layer 200 micron DFT offshore paint coating system as standard. Two cabin doors give full access to the operator compartment. The operator is sealed behind a glass window while operating the control panel.

The setup is suitable for cased hole slickline (up to 0.140”), braided line (up to ¼”) and monoconductor (up to ¼”) operations. The unit is standard equipped with a hoisting bar including manuel Hoist to exchange the winch drums.

A set of standard decals and ID plates, a small section of spare parts, a digital operation / maintenance manual / data book translated into customer’s language plus two days on-shore training and commissioning ex-works. The the Netherlands are part of the delivery.

The unit complies with the following standards, directives and regulations:

98/37/EC Machinery Directive

97/23/EC Pressure Equipment Directive

89/336/EC Electromagnetic Compatibility Directive.



**POWER PACK & WINCH**

## Specifications

Containerized 79 HP Double Drum ASEP wireline unit c/w Operators Cabin, spring starter suitable for zone II ISO 9001 c/w measuring device for 0.108” and 3/16” line with an in-built automatically charged BOP accumulator plus control panel to well head pressure control equipment equipped with:

- 20,000 Ft of 0.108” Bridon Wire – API. 9A
- 20,000 ft of 3/16” Stranded line
- 0-2000 lbs weight indicator
- 0-5000 lbs weight indicator
- Depth indicator (Imperial)

**Operating temperature range:** -20°C to +40°C

**Dimensions (LxWxH):** 1900x1450x2715 mm

**Transport weight:** 1040 kgs (excluding winch drums)



**ASEP SLICKLINE UNIT**